

Multi-Technology RS485 Reader

**WAR-MPX-485****Description:**

WAR-MPX-485 can be easily disinfected in areas where hygiene is important, and has an exceptionally long life due to no moving parts. The unit resists the elements such as glue, oil, rain, ice, snow. Ideal for hospitals, industrial and commercial application.

This dual-application product has advanced reader features for wide compatibility with different controller types including multiple RFID card transmission formats, LED & Buzzer control.

This superior quality Smart reader is rugged, weather-resistant and attractive in design. The product was designed to reduce stock levels.

Blue backlit LED assist operation in low or no light conditions. With the internal sounder, WAR-MPX-485 provides superior accessibility.

Features:

- Smooth attractive design, with allweather
- Blue backlit
- 1 LED with 2 colors and integral sounder for programming
- Green connector for wiring
- Multi Technology/Multi Format reader
- Communication Encryption: 3DES
- RS485 output, private protocol
- Manufactured in ISO:9001 registered facility

Specifications:

- Maximum read range: 50mm (2.00 in.)
- Modulation: ASK at 13.56MHz
- Output: RS485, 4 wires
- Distance to Panel: 1200m
- Compatible Cards: Mifare S50, S70, KK1208M1 CPU cards
- ISO14443A
- Operating Voltage: 7-12VDC
- Operating Current: ≤100mA
- Standby Current: ≤80mA
- Working Temperature: -30°C to 65°C (-22°F to 150°F)
- Operating Humidity: 0 to 95%
- LED Control Input: RS485 Protocol
- Buzzer Control Input: RS485 Protocol
- Dimensions: 98mm L x 42mm W x 18mm D
3.85" L x 1.63" W x 0.71" D
- Weight: 250g / 0.55lb



*All logos & trade marks represent the registered users only.
All rights reserved. All product specifications on this brochure
are subject to change without notice.*