

Time Attendance Terminal Standalone Controller



WAC-1D2T-MICRO
(Proximity EM Reader Built-in)



DESCRIPTION:

The **WAC-1D2T-MICRO**, (WatchNET, C Series, Standalone, 1 Doors, 2 Readers) is an advanced standalone allowing for the connection of external reader with REX Button for exit.


RANGE DESCRIPTION:

The WatchNET C Series access controllers consist of two different ranges (Access Control Panel, Standalone) which are interchangeable if required. Both can be used in a standalone or networked configuration mode, both ranges are compatible with the 3 Series Lift Controllers and Multi IO Controllers and both can be connected to a TCP/IP network.

FEATURES:

- 32 bit processor with 4M bit data memory
- Built-in EM Proximity, Reader (Optional)
- Blue backlight, TouchPad
- Cards holder capacity: 30,000 events
- Transactions storage: up to 15,000
- Work Mode: Card / Card + PIN
- OLED dual color display to indicate Clock, Company, Name, Card No
- Communication: TCP/IP
- Compatible with all Wiegand reader format from 24 to 72 Bits
- Events Flow Control
- Supports 500 Visitors
- Including UDP Protocol
- CE, FCC, RoHS approval

READER CONNECTORS:



Technical Specifications	
CPU	Texas Instrument ARM® Cortex-M3
Lock Output	1 Door Relay (NC/NO)
Door Sensor	1 Door Sensor (NO)
Request to Exit	1 Exit Button
Auxiliary Relay Output	1 Auxiliary Output Relay
Auxiliary Inputs	2 Auxiliary Inputs
Card Reader Input	1 Wiegand Reader Input
Communication	RS-232/RS-485 interface
Maximum number of Controllers on RS 485	Up to 127 controllers per RS-485 bus
Online Computer Polling	Supported
TCP Communication speed	100M
Time Groups	15 Time Groups for 1 door
Maximum Card Capacity	30,000
Emergency Cards	10
Transaction Storage	15,000 events
Maximum read range	E: 150mm, H: 10mm; M: 50mm (2.00 in.)
Compatible Cards	E: EM Proximity card
Modulation	EM: 125KHz
Communication Speed	10/100M
Operating Voltage	12VDC (±10%)
Operating Current	≤ 100mA
Standby Current	≤ 80mA
Working Temperature	-30°C to 65°C (-22°F to 150°F)
Operating Humidity	0 to 95%
Dimensions	117×86×22mm
Weight	290 g (0.63 lbs.)

All logos & trade marks represent the registered users only. All rights reserved.
All product specifications on this brochure are subject to change without notice.

CANADA:
351 Ferrier Street, Unit 5
Markham, ON L3R 5Z2
Toll Free: 1-866-843-6865
Tel: 416-410-6865
Fax: 1-866-331-3341

USA:
171 Cooper Ave. Suite 110
Tonawanda, NY 14150 USA
Toll Free: 1-855-404-3193
Local: 1-716-877-7277
Fax: 1-866-331-3341

info@watchnetaccess.com
www.watchnetaccess.com

INDIA:
RZ- 2, Ground Floor
Kapashera
Opp Kapashera Police Station
New Delhi-110037
Tel/Fax: +91 11 26816005

UAE:
P O Box 126312
No 703, Oxford Towers
Business Bay
Dubai, UAE
Tel: +971 4 2767117