

**2 Doors 2 Readers (In only)
POE Network Controller****WAC-X2D2R****Description:**

WAC Access Controllers are designed to be self-contained controllers ideally suited for small and medium sized companies. Packed with rich features, this product takes care of a variety of control and automation functions in addition to basic access control requirements of any facility.

The models have been designed for specific access requirements in any facility such as access by card and exit by push button. Based on the needs on site, the designer can choose from available models capable of controlling access to 1, 2, 4 or 8 doors (per panel).

The controllers communicate through the traditional RS485 Bus or TCP/IP. The controllers are capable of using industry standard 26-72 bit Wiegand readers as well as other related technologies.

The 2 Door controller can directly power up to 2 door strikes, when using maglocks an additional power supply is needed. 4 door or 8 door controllers require an additional power supply to operate maglocks and/or strikes.

Note local fire and building codes may apply when using maglocks.

Lockable cabinet and control board power supply included with the Access Control Kits.

WatchNET provides ease of installation with a wiring diagram printed on the cabinet door.

Weatherproof and IP rated controller cabinets are available.

Features:

- WatchNET-V4 Integrated Security Software with CCTV, intrusion, Biometric Integration, Enterprise-Global and Remote Access Capability
- Advanced ARM M4 Processor, High Speed Response-100,000 credentials in 0.1 sec
- POE 803.11af: A & B Format (End-Span & Mid-Span) with 600mA On Board and Backup Battery Connection
- Flow Control - Scenario Based Logical Event and I/O based configuration with mathematical algorithms
- Multi-Credential, Multi-Factor ID and other High-Security Options. Pay-Per-Swipe and many more capabilities
- Seamless Operation and Recovery for On-Line and Off-Line modes
- RS485 inter communication bus for local and global anti passback and lock down events in off-line mode
- New enclosure for easy mounting and status monitoring

Advanced Security Features:

- RS485 Encrypted Readers Compatibility
- Wiegand Readers Inputs - Full range 24-72 BIT, including proprietary readers
- Eleven different options for door access: Standard, Handicap, Multi-Card, Multi-Factor ID, Anti-Pass-Back, Supervisor-User, Multi-User-Group, Video-Verified by Guard, Manager, Master, Emergency

Salient Features of WatchNET Controllers:

Integrated Security Solution feature

- Access Control
 - ✦ Multi maps, Zoom In/Out
 - ✦ Multi modes: Card, PIN, Fingerprint, Face Recognition
 - ✦ Transaction will bring the map and cameras
- Intrusion (Support: DSC, Rocknet / ProSYS, Pima)
- CCTV (Compatible with Axis, Hikvision, WatchNET & CP PLUS...)

1. Smart Mobile APP

- Compatible with Android, IOS
- Management, Remote Control, Transactions...

2. POE

- POE
- Backup battery: POE will offer a socket for backup battery
- Low Voltages protection: Power off during 10.6V, stop to charge during 13.8V
- Network based, 10/100 M

3. 3 Layer Memory Structure & Processor

- 32 bits ARM Cortex M4 processor
- 3 Layer memory structure: SDRAM, RAM, Flash
- Download 30k card users, it will take less than 15 seconds

4. Supervisor

- DIP Switch to enable or disable SUPERVISOR
- Once the wire is cut, the system will alarm

6. Multi Language

- English, Hebrew, Spanish, Russian, Arabic
- Customer can add his own language by Language Editor of Application

7. Multi Database, Oracle as an option

- Supports Oracle database, much more stable during enterprise class installations
- Supports MS_SQL
- Supports MS_Access also, just for small installations

8. Flexible

- Multi connecting mode: TCP/IP, RS232, RS485

9. Select Events to Save

- If you would not like to see some unconsidered transactions, such as Door Relay Active..., you can choose "Not saved"

10. Events Drive Alarm / Lockdown

- Every event can be setup as the condition to active some relays or close some doors and open some rest doors

11. 8 Bytes card number length

- Up to 8 bytes card number length, much more security
- Supports all Wiegand readers from 26 bits to 72 bits

12. Supervisor / Manager card

- Boss card: can open any door anytime. Double swipe will switch the door status: NO / Normal
- Manager card: will not be limited by Anti-Pass back. Double swipe will switch the door status: NO / Normal

13. Handicap card

- Normal card: The door will keep open normal seconds, like 5 seconds
- Handicap card: The door will keep open longer, like 15 seconds



14. Emergency card

- Emergency card can open all doors when the system crashed

15. Multi-Mode to open door

- Card / PIN
- Card + PIN
- Card / Fingerprint
- Card + Fingerprint
- Multi cards: Up to 8 cards in short time, and release all cards after 8 seconds waiting

16. Master / Slave cards to open the door

- Everybody can setup a Master card for him
- Only this user and his master come here together to open the door

17. Groups cards to open the door

- Up to 4 groups
- Several cards of each group

18. Confirm by Monitor Center

- Only confirmed by center, then door will be open
- Special for Bank Money warehouse

19. Private PIN

- Everybody will have a private PIN: 4 to 8 digitals
- Private PIN will work as same as his card
- System will show his name when he use his PIN

20. Armed / Disarmed

- When all people leave, swipe card and press "Armed Code" from door reader, the system will be armed
- When the first people come, swipe card and press "disArmed Code", the system will be disarmed

21. Email notification

- Up to 3 pcs target email box for every transaction
- System will send email to these email box when the setting events happen

22. Calculator for special area

- Special for some place to calculate different kind of worker
- Show these worker number on display

23. Popup

- Popup for each event
- Different direction and symbol mention
- Different color for each event
- Different sound for each event

24. Operator

- Different management level
- Matched with doors
- Matched with department


25. Different view in different client

- Same view for some clients
- Different view for each client if you want
- Only show these panels which is connected to this PC



Controller Highlights:

- Supervised Inputs
- Biometric Integration
- Multi-Credential Access
- Dual Power - 12VDC or POE
- Primary/Secondary card options
- RS485 Reader Compatible (100m/328ft)
- Full Range Wiegand Reader Compatible
- Built-in Supervised backup battery charger
- Multi-Factor ID and Advanced Authentication

Model	WAC-X2D2R
	
Description	2 Door 2 Reader
Number of Readers	2
Reader Mix	2 pcs Wiegand or RS485, combines
Card Holders	100,000 Credential
Memorized Events	200,000 FIFO Events
Door Inputs	2 REX, 2 Door sensors
Door Outputs	2 SPDT (Single Pole Double Throw), Dry Contact
AUX Inputs	4 Configurable
AUX Outputs	2 SPDT (Single Pole Double Throw), Dry Contact
CPU	32 bits ARM® Cortex-M4 Processor
Memory	32 KB ROM / 512KB SRAM
Reader	RS485 Bus - 1 Wires up to 2 Readers Wiegand - 4-6 Wires, 12VDC 200mA Wiegand Format - 24-72 BIT multi-brands Supports Wiegand 24 to 72 bits (Fingerprint reader, EM/Mifare reader)
Comunnication	TCP/IP 100MBPS Auto Sensing, RS485 127 controllers for each RS485 Up to 1,200 m for each RS485 Communication speed:19,200/9,600/4,800 1,1,n
Backup Battery	POE Mode - 12VDC (non-charging) / 12VDC Mode - 12VDC / 7AH (charging)
Power Input	12VDC, 500mA
Protection Circuit	Protects the board from over voltage and short circuit
Auto-test	Yes
LED indicator light	Yellow: power; red and green: communication
POE	803.11af
Power Consumption (non-Poe)	12VDC (±10%), 200mA, (Controller Only) 12VDC (±10%), 2A MAX with 2 Wiegand Readers
Work Environment	0 - 95% RH, - 20°C ~ 65°C / - 4°F ~ -150°F
PCB Enclosure Weigh	4.5kg / 9.92lb
PCB Size	W45mm x H135mm x D58mm / W1.77" x H5.31" x D2.28"
Package	Metal housing with power supply
Dimension (mm)	40.3cm x 38.4cm x 7.2 cm / 15.8" x 15.1" x 2.8"

All logos & trade marks represent the registered users only. All rights reserved.
All product specifications on this brochure are subject to change without notice.

CANADA:
351 Ferrier Street, Unit 5
Markham, ON L3R 5Z2
Toll Free: 1-866-843-6865
Tel: 416-410-6865
Fax: 1-866-331-3341

USA:
171 Cooper Ave. Suite 110
Tonawanda, NY 14150 USA
Toll Free: 1-855-404-3193
Local: 1-716-877-7277
Fax: 1-866-331-3341

Rev Aug 13, 2018

info@watchnetaccess.com
www.watchnetaccess.com

INDIA:
RZ- 2, Ground Floor
Kapashera
Opp Kapashera Police Station
New Delhi-110037
Tel/Fax: +91 11 26816005

UAE:
PO Box 126312
No 703, Oxford Towers
Business Bay
Dubai, UAE
Tel: +971 4 2767117