

**MOBILE-READY PROXIMITY READER**



Mounts to mullion

Mounts to single-gang wall switch box

**WAR-BLU-HIT**



WAR-BLU-HIT is a proximity reader solution with mobile access support. Based upon the proven contactless digital radio frequency identification (RFID) platform, the reader interfaces with a wide range of electronic access control systems by complying with either the legacy Wiegand equipment or the latest bi-directional Open Supervised Device Protocol (OSDP). In addition to traditional proximity credentials, such as clamshell cards and key tags, the platform also offers the option of mobile access credentials loaded on Bluetooth Low Energy (BLE) enabled smartphones. This allows the smartphone to function as a contactless electronic access control credential.

Mobile Smart phone  
Access Control Solution



**Frequency:** 125 KHz and 2.4 GHz  
**Read Range:**  
Physical Credentials: Up to 4 inches (102mm)  
Mobile Credentials: Up to 12 inches (306mm)



**Bluetooth Low Energy**  
Supports Smart phone  
Mobile Access Credentials



**Wiegand**  
Output Interface



**Single Reader for Mullion or Wall-Switch Mount**  
Metal Door, Window Frames & Flat Surfaces

\* OSDP readers are independent models and need to be appended with the suffix "-OSDP" when ordering

Specifications	Mobile-Ready Proximity Reader
Technology	Proximity and Bluetooth Low Energy (BLE)
Frequency	125 kHz (proximity) and 2.4 GHz (BLE)
Mounting	A single reader for metal door and window frames, single-gang wall boxes, and flat surfaces
Dimensions	Mullion: 1.7" W × 4.7" H × 1.2" D (43 mm × 119 mm × 30 mm) Switch Plate: 3" W × 5.1" H × 1.2" D (76 mm × 130 mm × 30 mm)
OEM Label Area	Backlit; Dimensions 0.9" W × 0.35" H (22.86 mm × 8.89 mm) with corner radius of 0.06" (1.5 mm)
Certifications	FCC, ICC, CE
IP Code	IP67
Voltage	+8 – 14 VDC
Current Draw	60 mA typical @ 12 VDC, 90 mA peak
Read Range	Physical Credentials: Up to 4 inches (102mm) Mobile Credentials: Up to 12 inches (306mm)
Cabling	24 AWG minimum, multiconductor stranded with an overall foil shield
Interface	Wiegand (26-bit)
Operating Temperature	–31°F to 150°F (–35°C to +66°C)
Audio Tone	Beeper included standard
Indoor & Outdoor Installation	Electronics sealed in weather and tamper-resistant epoxy potting
LED	Five-state standard (blue, red, green, amber, and off)
Keypad Output	Either Wiegand or OSDP
Technologies Supported	WatchNET Certain HID® 125-kHz Proximity protocols + certain AWID® 125-kHz Proximity Protocols WatchNET Access Mobile Access Credentials

**NOTES:**

- 1 Optimized for use with devices supporting BLE version 4.2.
- 2 Self evaluated.
- 3 Linear power supplies are recommended for best operation.
- 4 8-Bit Burst or 26-bit Wiegand standard.
- 5 WatchNET Mobile Access Credentials are intended to be supported by the current and preceding versions of Apple® iOS and standard compliant Google Android™ mobile operating software (OS). Custom OS variants may result in a loss of functionality.

*All logos & trade marks represent the registered users only. All rights reserved.  
All product specifications on this brochure are subject to change without notice.*

**CANADA:**

351 Ferrier Street, Unit 5  
Markham, ON L3R 5Z2  
Toll Free: 1-866-843-6865  
Tel: 416-410-6865

**USA:**

171 Cooper Ave. Suite 110  
Tonawanda, NY 14150 USA  
Toll Free: 1-866-843-6865  
Local: 1-716-877-7277

**UAE:**

P O Box 126312  
No 703, Oxford Towers  
Business Bay, Dubai, UAE  
Tel: +971 4 2767117

Division of WatchNET Inc.

**WatchNET®**

Rev. Sep.24 2021

info@watchnetaccess.com  
www.watchnetaccess.com